

Convertible "Mystique™" Instruction Sheet

Read All Instructions Before Assembling Crib. Keep Instructions For Future Use.

PARTS LIST (A PHILLIPS HEAD SCREWDRIVER AND A FLAT-HEAD SCREWDRIVER IS REQUIRED)

- | | |
|---|---|
| BF) 1 Back Frame (largest) | AW) 1 Allen Wrench (included) |
| FF) 1 Front Frame (with Drop Gate attached) | HW) 1 Hex Wrench (included) |
| DG) 1 Drop Gate (attached to Front Frame) | TL) 2 Trigger Latches (attached to Drop Gate) |
| SF) 2 Side Frames | SP) 2 Strike Plates (attached to Front Corner Post) |
| FP) 2 Front Corner Posts (with Strike Plates) | H) 1 Hinge (attaches Drop Gate to Front Frame) |
| BP) 2 Back Corner Posts (without Strike Plate) | TP) 6 Tension Pins (1¼" Gate Pins) |
| YR) 1 Youth Rail (Youth Bed Kit) | ABR) 2 Adult Bed Rails (Conversion kit not included with crib) |
| SH) 2 Short Posts (for Adult Bed conversion) | CD) 8 Cross Dowels (to attach Adult Bed rails) |
| MS) 1 Mattress Support (Spring) | |
| B90) 8 90 Millimeter Bolts | |
| B60) 8 60 Millimeter Bolts | |
| B½) 4 Spring Bolts | |



BF) Back Frame



FF) Front Frame



SF) Side Frame



TL) Trigger Latch



B1) Small Spring Bolts




FP) Front Corner Posts



BP) Back Corner Posts



SH) Short Posts



90mm Bolt

60mm Bolt



SP) Strike Plate



GP) 1¼ inch Gate Pin




AW) Allen Wrench



MS) Mattress Support



YR) Youth Rail



ABR) Adult Bed



HW) Hex Wrench



ABR) End View

CRIB ASSEMBLY INSTRUCTIONS

Step 1: Attach Back Posts (BP) to Back Frame (BF) using four 90mm Bolts (B90). You may find it easier to lay the Back Frame (BF) on the floor for this step. **Do not fully tighten the bolts at this time.**



Step 2: For the next step you will need two 60mm Bolts (B60). Stand up the Back Frame (BF) with the Back Corner Posts (BP) attached. Attach a Side Frame (SF) to one of the Back Corner Posts (BP) using two 60mm Bolts (B60). **(Do not fully tighten the bolts at this time.)**



Step 3: Repeat Step 2 for the other side.

Step 4: For the next step you will need a Front Corner Post (FP), the Front Frame (FF) and two 90mm Bolts (B90). You will now need to attach one of the Front Corner Posts (FP) to one end of the Front Frame (FF) using two 90mm Bolts (B90). Make sure that the profiles on the Front Corner Posts (FP) and the Front Frame (FF) match. **Do not fully tighten the bolts at this time.**

Step 5: Repeat Step 4 for the other side.



Step 6: Now you will need to attach the Front Assembly (Front Frame & Corner Posts) to the three sided Back and Side Frame assembly. For this step you will need four 60mm Bolts (B60). **Do not fully tighten the bolts at this time.**

Step 7: To complete the assembly of the crib, you must now tighten all of the bolts. **(Make sure that the ends of all frames are flush with the tops of the posts).** Before fully tightening bolts, stand the Front assembly up to let the Front Frame (FF) drop to the bottom of the holes.

Step 8: Lower the Mattress Support (MS) into the crib. You have three levels of height adjustment for your Mattress Support (MS). Use the four Spring Bolts (B 1/2) to bolt the Mattress Support (MS) to the crib. The Spring Bolts (B 1/2) will bolt into the Height Adjustment inserts located in the posts. Use the Hex Wrench (HW) to tighten all Spring Bolts (B 1/2).

Once a crib has been converted to a youth bed or adult bed it is not intended to be converted back to a crib.

YOUTH BED ASSEMBLY INSTRUCTIONS

STARTING FROM CRIB:

- Step 1:** Remove the Front Frame (FF) and leave the Front Corner Posts (FP) on the bed.
- Step 2:** Make sure that the Mattress Support (MS) is secured to the lower Height Adjustment insert on the four Corner Posts.
- Step 3:** To attach the Youth Rail (YR) you must first hammer in one Tension Pin (TP) $\frac{3}{4}$ " deep into each end of the Youth Rail (YR) into the pilot holes.
- Step 4:** Now you must insert the Tension Pins (TP) located in the ends of the Youth Rail (YR) into the holes in the Front Corner Posts (FP). Use two 90mm Bolts (B90) to bolt the Youth Rail (YR) to the Front Corner Posts (FP). Tighten both bolts.
- Step 5:** Remove Strike Plates (SP) located at the top of the posts.



STARTING FROM SCRATCH:

- Step 1:** Follow Steps 1 through 3 of the Crib assembly instructions.
- Step 2:** Attach one Front Corner Post (FP) to one Side Frame (SF) using two 60mm Bolts (B60).
- Step 3:** Repeat Step 2 for the other side.
- Step 4:** Follow Step 8 of the crib assembly instructions.
- Step 5:** Follow Steps 2 through 5 of the Youth Bed assembly instructions (starting from crib).

YOUTH BED GUARD RAIL INSTRUCTIONS

- Step 1:** Use the above instructions to convert your crib into a Youth Bed.
- Step 2:** Unscrew the Hinge (H) on the Front Frame (FF) and detach the Drop Gate (DG).
- Step 3:** Detach the 2 Trigger Latches (TL) from both ends of the Drop Gate (DG).
- Step 4:** Loosen the 60mm Bolts (B60) that bolted the Youth Rail (YR) to the Front Corner Posts (FP).
- Step 5:** Hammer the Tension Pins (TP) $\frac{3}{4}$ " deep into the pilot holes on the two ends of the Drop Gate (DG).
- Step 6:** Insert the four Tension Pins (TP) on the Drop Gate (DG) into the four pilot holes on the inside of the Front Corner Posts (FP).
- Step 7:** Tighten the 60mm Bolts (B60) that bolt the Youth Rail (YR) to the Front Corner Posts (FP).



FULL SIZE BED ASSEMBLY INSTRUCTIONS

- Step 1:** Remove the Drop Gate (DG) from the Front Frame (FF) by unscrewing the Hinge (H).
- Step 2:** Attach the Short Posts (SP) to the Front Frame (FF) using four 90mm Bolts (B90).
- Step 3:** Attach the Rear Corner Posts (RP) to the Back Frame (BF) using four 90mm Bolts (B90).
- Step 4:** Connect the Headboard and Footboard with Wooden Adult Bed Rails (ABR). Make sure that the Mattress Support cleats are on the upper side of the rails. Eight Cross Dowels (CD) are provided for assembly. Insert the Cross Dowels (CD) into the holes located on the inside edge of the Adult Rails (ABR). To attach the Adult Rails (ABR) to the Headboard and Footboard you must use the eight 60mm Bolts (B60) provided. Fully tighten all bolts. *Metal rails are also available from Baby's Dream Furniture.



FOR FUTURE USE AND REFERENCE

RETAIN THIS INSTRUCTION SHEET AND THE CRIB TOOLS IN THE ORIGINAL SACK AND SECURE IT TO THE SPRING UNDER THE MATTRESS WITH PLASTIC TIES.

CARE INSTRUCTIONS: The natural warmth of wood is a lasting value. Character marks, checking and grain variations are part of the beauty of wood and, therefore, should not be a concern. If treated with care, this solid wood product will last you for many years to come. Once every week, wipe your Baby's Dream furniture with Pledge®, lemon oil or other similar wood treatment products. If you encounter any roughness in the finish of your new crib, fold a piece of regular white paper—not tissue or newspaper—and rub it gently against the surface until the desired smoothness is achieved. If refinishing, use a non-toxic finish specified for children's products. Let dry, sand with a very fine product such as folded paper or dish washing sponge and, finally, apply water-based baby-safe lacquer for the perfect matching shine.

WARNING!

To insure your child's safety and for your own peace of mind, be sure to follow instructions properly. Failure to follow these warnings and assembly instructions could result in serious injury or death. Before each usage or assembly, inspect the crib for damaged hardware, loose joints, missing parts or sharp edges.

- ✓ **DO NOT** use the crib if any parts are missing or broken.
- ✓ **DO NOT** substitute parts. Ask your dealer or write to Baby's Dream Furniture for replacement parts and instructional literature if needed.
- ✓ Make sure that all bolts and screws are properly tightened. **DO NOT** over- or under-tighten.
- ✓ **AVOID STRANGULATION:** As soon as an infant can sit or stand up, close the crib gate or raise the Drop Front permanently.
- ✓ **DO NOT** place the crib near a window where cords from blinds or drapes may strangle a child.
- ✓ **DO NOT** tie pacifiers, necklaces or any other items around a child's neck or on the crib parts.


WARNING!

Strings can cause strangulation! Do not place items with string around a child's neck, such as hood strings or pacifier cords. Do not suspend strings over a crib or attach string toys.

- ✓ **NEVER** use plastic shopping bags or other film as mattress covers, because they can cause suffocation.
- ✓ For a newborn, adjust the spring on the highest level of the Height Adjuster and open the gate or lower the Drop Front for easy access.
- ✓ **DO NOT** leave a child in a crib with an open gate or lowered Drop Front. Be sure the gate is closed or the Drop Front is raised and locked in position whenever the child is in the crib. After closing the gate or raising the Drop Front, make sure the latches are secure.
- ✓ The child must be seated at the rear of the crib when lowering or raising the gate or Drop Front.
- ✓ As your child grows, adjust the height of the spring down so that he/she cannot pull himself/herself out of the crib. When the child is able to pull to a standing position, set the mattress to the lowest position and remove bumper pads, large toys and other objects that could serve as steps for climbing out. When the child is able to climb out or reaches the height of 35" (90cm), the bed should no longer be used in the form of a crib. You can continue to use this crib as a youth or toddler bed for another 2 to 3 years by using the **Youth Bed Conversion Kit**.

ANY MATTRESS USED IN THIS CRIB MUST BE AT LEAST 27¹/₄" X 51⁵/₈" WITH A THICKNESS NOT EXCEEDING 6". DO NOT USE A WATER MATTRESS WITH THIS CRIB.

This crib conforms to the applicable regulations promulgated by the Consumer Product Safety Commission.



This product may be covered by one or more of the following patents: D366,778; D366,970,5,077,846 and other patents pending.



BABY'S DREAM
FURNITURE, INC.

Buena Vista, GA 31803-0579
www.babysdream.com

